Kolzer

MILANO ITALIA

BASE COAT - 525 pre-metallization

VARNISH FOR VACUUM METALLIZATION OF PLASTIC MATERIALS

CHARACTERISTICS: This product can be used in different applications, in particular for polystyrene, ABS and thermosetting composition like resin: it confers a remarkable brightness to the varnished items and has moreover an high filling and self levelling power on raw surfaces.

APPLICATION: Use the product just as it is furnished. Use it as spray with manual and automatic system. In case of particular dilution exigency, will be our care to give you the right thinner.

DRYNG: After drying 525 in the air for some minutes, dry it up in the oven at 50 – 60°C for 45 minutes. Once it is complete dried, the 525 presents excellent adhesion on surface, resistance to the abrasion, to the water, to detergents and to chemical and atmospheric agents.

STORAGE: We recommend, for a good utilisation of the product, to keep in store 525 for no more than 6 months. The recommended temperature must be between 10°C and 30°C. Keep containers perfectly sealed. The guarantee is conditioned to the respect of the above storage conditions.

PACKAGING: Drums Kg. 19
Drums Kg. 200

The above information and suggestions are to be considered indicative, they can be modified to better fit our products to material and their surfaces. The above specifications are given without our responsibility because the use conditions are beyond our control.

April 2003